

AD715780

October 1970

FLUID MECHANICS LABORATORY



This document has been approved
for public release and sale; its
distribution is unlimited.

DDC
RECEIVED
DEC 19 1970

DEPARTMENT OF MECHANICAL ENGINEERING
MASSACHUSETTS INSTITUTE OF TECHNOLOGY

Reproduced by
**NATIONAL TECHNICAL
INFORMATION SERVICE**
Springfield, Va 22151

INFRARED DIFFERENCE-FREQUENCY GENERATION
USING A TUNABLE DYE LASER

by

C. Forbes Dewey, Jr. and Lon O. Hocker

Fluid Mechanics Laboratory
Department of Mechanical Engineering
Massachusetts Institute of Technology

This research was supported in part by the Advanced Research Projects Agency of the Department of Defense, monitored by the Office of Naval Research under Contract No. N0014-67-A-0204-0040 and ARPA Order No. 322.

This document has been approved for public release and sale; its distribution is unlimited.

INFRARED DIFFERENCE-FREQUENCY GENERATION
USING A TUNABLE DYE LASER

C.F. Dewey, Jr. and L.O. Hocker
Massachusetts Institute of Technology
Cambridge, Massachusetts

ABSTRACT

Intense infrared radiation has been produced in the $3\mu - 4\mu$ region by generating the difference frequency between a wavelength-tunable dye laser and a Q-switched ruby laser. Saturation of the conversion of ruby photons to sum-and-difference frequencies was observed on a single pass through a phase-matched LiNbO_3 crystal. The system appears to be attractive as a simple, highly-efficient, and broadly-tunable infrared source.

Considerable interest exists in producing intense, wavelength-tunable radiation throughout the optical spectrum. Although notable success has been achieved in the near-ultraviolet, visible, and near-infrared using dye lasers¹ and parametric oscillators², the results of experiments at infrared wavelengths have been less spectacular.

Tunable far-infrared difference frequencies have been produced by Faries, Gehring, Richards, and Shen³, following earlier theoretical and experimental work by Laine⁴, Zernike, and Berman⁵, Yajima and Inoue⁶ and others⁷. To date, these efforts have been directed to the far-infrared ($\lambda > 100\mu$). In addition to difference-frequency generation, two important methods of using the Raman effect to produce infrared radiation have been reported recently. R. Pantell⁸ and co-workers at Stanford have used non-linear crystals and intense ruby light to yield simultaneous Raman-shifted visible light and infrared difference radiation. The resulting infrared radiation is continuously tunable over the spectral region 50 - 250 μ . Patel and Shaw⁹ have used a magnetically-tunable Raman shift to convert the output of a 10.6 μ CO₂ laser into a coherent beam between 10.9 μ and 13.0 μ with substantial efficiency. These two methods appear very promising.

Our efforts have been directed to producing intense infrared emission in the 2 μ - 20 μ spectral region. The optical system is shown in Fig. 1. The output of an unpolarized Q-switched ruby laser is divided into two parts by a beamsplitter. One beam is used to pump a wavelength-tunable dye laser. The output of the dye laser is then combined with the second part of the ruby beam by a dichroic mirror and the composite radiation is directed into a phase-matched LiNbO₃ crystal.

A silicon filter is used to block completely all emerging radiation at the ruby and dye wavelengths, while passing a substantial fraction of the infrared difference frequency. A liquid-nitrogen cooled PbSe detector was used to measure the infrared output, with appropriate attenuators being used to avoid saturating the detector.

The results of our initial experiments are presented in Figs. 2 and 3. The infrared power is seen to be (a) linearly proportional to the ruby power entering the crystal, and (b) independent of the power of the dye laser beam above a well-defined threshold.

The LiNbO_3 crystal was rotated to achieve phase-matching at an angle

$$\theta_{\text{IN}} \approx \sin^{-1} \left[\frac{n_o^p - n_o^d + (n_o^d - n_o^i)(\lambda_p/\lambda_i)}{n_o^p - n_e^p} \right]^{1/2}$$

where θ_{IN} is the angle from the optic axis at which phase-matching occurs (as measured inside the crystal). The superscripts (p, d, i) on the index of refraction, n , denote values at the pump, dye, and infrared wavelengths, respectively. Subscripts o and e refer to the ordinary and extraordinary indices of refraction. The incident radiation made a single pass through the nonlinear crystal; no optical cavities were employed. The experiment was conducted at ambient temperatures which were subject to random excursions of 3 - 5°C, with no apparent effect on the stability of the output amplitude.

The experimental data shown in Figs. 2 and 3 were obtained with a concentrated DTTC Iodide/DMSO dye solution in a transversely-pumped dye laser. The dye laser output could be varied from about 0.84μ to

0.89 μ by using a diffraction grating as the rear cavity reflector. Other dyes are available which cover the entire wavelength region 0.72 μ - 1.2 μ . An output mirror of 30% reflectivity was used on the dye cell. The spectral width of the dye laser radiation was roughly 3 - 5 cm^{-1} , although significantly narrower lines are feasible. Approximately 6 KW of infrared power was produced at the detector for an initial power of 4 MW of total unpolarized ruby radiation. We estimate that the conversion of available ruby photons (of the correct polarization) to infrared photons substantially exceeded 1%, in spite of visible curvature of the polished crystal faces. The spectral width of the infrared emission was less than 10 cm^{-1} . Because the dye laser operates only during the ruby pulse, synchronization of the two laser pulses is assured.

In order to confirm the infrared output wavelength and demonstrate the flexibility of the tuning arrangement, we scanned the 3.5 μ absorption band of an 0.2 mm thick sheet of polyethelene. The result is shown in Fig. 4. The data points are compared to an IR spectrometer tracing obtained on a standard dual-beam instrument. The wavelength shown for each data point was computed as the difference wavelength between the measured dye laser output and the ruby output at 0.6943 μ . The discrepancy at 3.69 μ is real; the spectrophotometer apparently did not resolve the transmission peak.

The present experimental system is limited to the spectral region below 4.5 μ by the transmission characteristics of LiNbO_3 . Proustite ($\text{Ag}_3\text{As}_5\text{S}_3$) and pyragyrite (Ag_3SbS_3) appear promising as useful non-

linear mixing media which will extend the available wavelength coverage to at least $13\mu^{10,11}$. The ruby second harmonic (0.347μ) and a continuously tunable dye laser operating from $0.4\mu - 0.7\mu$ would be capable of covering the wavelength region from 0.7μ to 2μ .

It should be noted that the available radiation at the dye laser wavelength is also increased by the nonlinear difference frequency generation. Both the near-infrared and infrared beams are available for spectroscopic purposes.

We are indebted to R.M. Hilton and the Air Force Cambridge Research Laboratories for supplying the LiNbO_3 crystal we used. This work was supported by the Advanced Research Projects Agency and Office of Naval Research.

1. The first organic dye lasers were reported by P.P. Sorokin and J.R. Lankard [IBM J. Res. Dev., 10, 162 (1966)], and by F.P. Schaefer, W. Schmidt, and J. Volze [Appl. Phys. Lett., 9, 306 (1966)]. Recent review articles have been published by B.B. Snavely [Proc. IEEE, 57, 1374 (1969)] and H.W. Furamoto and H.L. Ceccon [IEEE J. Quant. Elect., QE-6, 262 (1970)].
2. J.A. Giordmaine and R.C. Miller, Phys. Rev. Lett., 14, 973 (1965). For more recent results, see, e.g.: J.E. Murray and S.E. Harris, J. Appl. Phys., 41, 609 (1970); E.O. Ammann, J.M. Yarborough, M.K. Oshman, and P.C. Montgomery, Appl. Phys. Lett., 16, 309 (1970).
3. D.W. Farries, K.A. Gehring, P.L. Richards, and Y.R. Shen, Phys. Rev., 180, 363 (1969).
4. D.C. Laine, Nature, 191, 795 (1961)
5. F. Zernike and P.R. Berman, Phys. Rev. Lett., 15, 999 (1965); see also F. Zernike, Phys. Rev. Lett., 22, 931 (1969).
6. T. Yajima and K. Inoue, Phys. Lett., 26A, 281 (1968).
7. N. Van Tran and C.K.N. Patel, Phys. Rev. Lett., 22, 463 (1969)
8. R. Pantell, presentation at U.S. Army Microwave Conference, June 10, 1970 (unpublished). See also: B. Johnson, R. Pantell, H. Puthoff, J. SooHoo, S. Sussman, and J.M. Yarborough, Proc. Int. Quant. Elect. Conf., Tokyo, September 1970, p. 140.
9. C.K.N. Patel and E.D. Shaw, Proc. Int. Quant. Elect. Conf., Tokyo, September 1970, p. 278.

10. K.F. Hulme, O. Jones, P.H. Davies and M.V. Hobden, Appl. Phys. Lett., 10, 133 (1967).
11. W.B. Gandrud, G.D. Boyd, J.H. McFee, and F.H. Wehmeier, Appl. Phys. Lett., 16, 59 (1970).




Figure 1. Experimental system for generating difference frequencies.




Figure 2. Infrared output power as a function of ruby laser excitation.




Figure 3. Infrared output power as a function of dye laser excitation.




Figure 4. Absorption spectra of polyethylene. Solid curve: conventional dual-beam spectrophotometer. Data points: measured transmission of infrared emission from crystal with wavelength computed from the measured dye and ruby laser wavelengths.

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) M.I.T., Cambridge, Mass.		2a REPORT SECURITY CLASSIFICATION Unclassified	
		2b GROUP	
3 REPORT TITLE Infrared Difference-Frequency Generation Using a Tunable Dye Laser			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5 AUTHOR(S) (Last name, first name, initial) C. Forbes Dewey, Jr. and Lon O. Hocker			
6 REPORT DATE October, 1970		7a TOTAL NO. OF PAGES 11	7b NO. OF REFS 11
8a. CONTRACT OR GRANT NO.		8b ORIGINATOR'S REPORT NUMBER(S)	
b. PROJECT NO. ONR Contract No. N0014-67-A-0204-004		Fluid Mechanics Laboratory Publication No. 70-11	
c. (ARPA Order No. 322)		8c OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. AVAILABILITY/LIMITATION NOTICES Distribution Unlimited			
11. SUPPLEMENTARY NOTES		12 SPONSORING MILITARY ACTIVITY Advanced Research Projects Agency Dept. of Defense and Office of Naval Research, Washington, D.C.	
13. ABSTRACT Intense infrared radiation has been produced in the 3 μ - 4 μ region by generating the difference frequency between a wavelength-tunable dye laser and a Q-switched ruby laser. Saturation of the conversion of ruby photons to sum-and-difference frequencies was observed on a single pass through a phase-matched LiNbO ₃ crystal. The system appears to be attractive as a simple, highly-efficient, and broadly-tunable infrared source.			

DD FORM 1 JAN 64 1473

Unclassified

Security Classification

14	KEY WORDS	LINK A		LINK J		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	lasers infrared radiation difference-frequency generation dye lasers nonlinear optics						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.